



NOTES:

MATERIAL:

Insulator: High Temperature Thermoplastic, UL 94V-0.
 Contact: Copper Alloy
 Shell: STAINLESS

PLATING:

Contact: Plated 30u'' Ni Overall Contact Au 1U
 Shell: Plated 30u'' Ni Overall
 Plated 1u''Au Selective Contact Area

Electrical:

Current Rating : 1.0 A AC/DC max.
 Voltage Rating : 30V AC/DC
 Ambient Temperature Range :-20° C~+60° C
 Storage Temperature Range :-40° C~+70° C
 Ambient Humidity Range :95% R. H. Max.
 Contact Resistance:100mΩmax.
 Insulation Resistance:1000Ωmin./500VDC
 Mating Cycles: 3000Insertions
 Temperature: 260° C ±5°

龙创中业电子科技(东莞)有限公司



DATE 2014/3/27

TOLERANCES UNLESS	
X. ± 0.50	X° ± 3'
.X ± 0.38	.X° ± 2'
.XX ± 0.25	.XX° ± 1'
.XXX ± 0.10	.XXX° ± 0.5'

TITLE: 产品名称	SIM PUSH 8+2P H1.8
PART NUMBER: 零件编号	LCZY-102012902
DRAWING NUMBER: 图纸编号	

UNIT 单位	mm	DESIGNED 设计	罗正富
SCALE 比例	1:1	CHECKED 核准	罗利斌
SHEET 页码	1/1	APPROVED 审批	张华宇