



NOTE:  
 Rating: DC 30V 0.1A  
 Operating Force:  $20 \pm 10$ gf  
 Lifetime: 50,000 Cycles

⑤	Contact Spring	—	1	Be Alloy	Ag Plated	—
④	Terminal	—	2	Phosphor Bronze	Ag Plated	—
③	Cover	—	1	SUS	Natural	—
②	Housing	—	1	LCP	Black	—
①	Slider	—	1	PA46	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	TITLE:
DRAWN		2019.9.30	DETECTOR SWITCHS
CHECKED			
APPROVALS			
TOLERANCES ARE			

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
APPROVALS DRAWN: S.L.L. DATE: 2019.9.30 CHECKED: _____ APPROVALS: _____ TOLERANCES ARE: 30~12.5 ±0.30 ANGLE PART NO. K5-1617SA-01 10~30 ±0.20 UNIT: mm SCALE: 1:1 PROJ:  PROJ: 5~10 ±0.15 ±2' DRAWING NO. SHEET 1 OF 1 ~5 ±0.10						